

SmartLogger3000A



Smart

Smart zero export control design



Simple

Easy to install on site



Reliable

Safety by lightning protection module

| Technical Specification | SmartLogger3000A00GL |
|--|---|
| Device Management | |
| Max. Number of Manageable Devices ² | 80 |
| Communication Interface | |
| WAN | WAN x 1, 10 / 100 / 1000 Mbps |
| LAN | LAN x 1, 10 / 100 / 1000 Mbps |
| RS485 | COM x 3, 1200 / 2400 / 4800 / 9600 / 19200 / 115200 bps, 1000 m |
| Digital / Analog Input / Output | DI x 4, DO x 2, AI x 4 |
| Active DO | 12V, 100mA (connection with relay, sensor) |
| Communication Protocol | |
| Ethernet | Modbus-TCP, IEC 60870-5-104 |
| RS485 | Modbus-RTU, IEC 60870-5-103 (standard), DL / T645 |
| Interaction | |
| LED | LED Indicator x 3 – RUN, ALM, 4G ¹ |
| WEB | Embedded Web |
| USB | USB 2.0 x 1 |
| APP | FusionSolar APP Communicated by WLAN for Commissioning |
| Environment | |
| Operating Temperature Range | -40°C ~ 60°C (-40°F ~ 140°F) |
| Storage Temperature | -40°C ~ 70°C (-40°F ~ 158°F) |
| Relative Humidity (Non-condensing) | 5% ~ 95% |
| Max. Operating Altitude | 4,000 m (13,123 ft.) |
| Electrical | |
| AC Power Supply | 100 V ~ 240 V, 50 Hz / 60 Hz |
| DC Power Supply | 12V / 24 V |
| Power Consumption | Typical 8 W, Max. 15 W |
| Mechanical | |
| Dimensions (W x H x D) | 225 x 160 x 44 mm (8.9 x 6.3 x 1.7 inch, without mounting ears and antenna) |
| Weight | 2 kg (4.4 lb.) |
| Protection Degree | IP20 |
| Installation Options | Wall Mounting, DIN Rail Mounting, Tabletop Mounting |

*1: 4G is not available in this model.

*2: Devices refer to: Inverter, meter, weather station devices and so on.